

SHAKING WATER BATH

The high-performance **SHAKING WATER BATH** with its advanced features & user-friendly design

FTSWB series models

FEATURE

This distinguished FTSWB model series of Shaking Water Bath are openly recognized by our worldwide end-users as the most suitable & high efficiency equipment for a large variety of laboratories that carry out industrial, pharmaceutical, clinical and biomedical experiments which need accuracy and uniformity with temperature control.



GENERAL SPECIFICATIONS

Temp. Range	Amb +5 °C to 98 °C
Temp. Accuracy	±0.1 °C at 37 °C
Temp. Controller	Digital PID controller
Temp. Sensor	PT-100 Ω
Timer Range	99 Hr 59 Min
Timer Controller	Digital display
Bath Internal Material	Stainless steel
External Material	Steel plate with powder coating
Heater	Stainless steel
Speed Range	50~200 rpm
Speed Control	Digital display
Stroke	Range : 15~20 mm
Standard Plate	Spring rack
Shaking Motion	Reciprocal
Safety Device	Over current circuit breaker
Motor	DC motor
Power	AC 220 V, 50/60 Hz

INDIVIDUAL SPECIFICATIONS PER MODEL

MODELS	FTSWB-830	FTSWB-845
Capacity	30 Liters	45 Liters
Bath Dimension (L x D x H) (mm)	500 x 300 x 250	600 x 300 x 300
External Dimension (L x D x H) (mm)	690 x 340 x 340	790 x 340 x 390
Heater Capacity	2 KW	2.5 KW